(Page I of 3)

State of California AIR RESOURCES BOARD

EXECUTIVE ORDER A-325-6-1 Relating to Certification of New Motor Vehicles

GFI CONTROL SYSTEMS, INC.

Pursuant to the authority vested in the Air Resources Board by the Health and Safety Code, Division 26, Part 5, Chapter 2; and

Pursuant to the authority vested in the undersigned by Health and Safety Code Sections 39515 and 39516 and Executive Order G-45-9;

IT IS ORDERED AND RESOLVED: That 1998 model-year GFI Control Systems, Inc. exhaust emission control systems are certified as described below for medium-duty vehicles:

Emission Standard Category: Low-Emission Vehicle (LEV)

Fuel Type: Dual-Fuel Liquefied Petroleum Gas (LPG) or Gasoline (Indolene)

Engine Family: WG9XA05.45BF Displacement: 5.4 Liters (326 Cubic Inches)

Exhaust Emission Control Systems & Special Features:

Dual Three Way Catalytic Converters (two)
Dual Heated Oxygen Sensors (two)
Exhaust Gas Recirculation
Sequential Multiport Fuel Injection

Vehicle models, transmissions, engine codes and evaporative emission control families are listed on attachments.

The non-methane organic gases (NMOG), carbon monoxide (CO), oxides of nitrogen (NOx), and formaldehyde (HCHO) LEV certification exhaust emission standards for this engine family in grams per mile are: (The standards in parentheses are for gasoline.)

Test Weight (1bs.)	Miles	NMOG	CO	NOx	<u>нсно</u>	CO (20°F)
3751-5750	50,000	0.160 (0.32)	4.4 (4.4)	0.4 (0.4)	0.018 (0.018)	12.5 (12.5)
	120,000	0.230 (0.46)	6.4 (6.4)	0.6 (0.6)	0.027 (0.027)	n/a

Reactivity Adjustment Factor (RAF) for NMOG Mass Emission: 0.50 (LPG) 1.00 (Indolene)

The certification exhaust emission values set forth for NMOG reflect application of a 0.50 or 1.00 RAF for 1998 model-year LEVs. The LEV certification exhaust emission values for this engine family in grams per mile are: (The values in parentheses are for gasoline.)

Test Weight (1bs.)	<u>Miles</u>	NMOG	CO	NOx	<u>нсно</u>	CO (20°F)
3751-5750	50,000	0.039 (0.13)	4.4 (1.9)	0.4 (0.2)	0.001 (0.001)	3.3 (3.0)
	120,000	0.045 (0.14)	5.2 (2.0)	0.4 (0.2)	0.001 (0.001)	n/a

BE IT FURTHER RESOLVED: That the manufacturer shall not be subject to the phase-in requirement as specified in Title 13, California Code of Regulations, Section 1960.1(h)(2) Endnote (10)(d) applicable to small-volume manufacturers of medium-duty vehicles.

BE IT FURTHER RESOLVED: That the vehicle manufacturer is certifying the listed vehicle models to the running loss and useful life standards applicable to 1995 and subsequent model-year vehicles in the "California Evaporative Emission Standards and Test Procedures for 1978 and Subsequent Model Motor Vehicles," and the listed vehicle models comply with those standards.

BE IT FURTHER RESOLVED: That the listed vehicle models also comply with the Board's "Specifications for Fill Pipes and Openings of Motor Vehicle Fuel Tanks" for the aforementioned model year (Title 13, California Code of Regulations, Section 2235).

BE IT FURTHER RESOLVED: That the listed vehicle models also comply with the Board's high-altitude requirements and highway emission standards, and with the California Inspection and Maintenance emission standards in place at the time of certification, as stipulated in "California Exhaust Emission Standards and Test Procedures for 1988 and Subsequent Model Passenger Cars, Light-Duty Trucks, and Medium-Duty Vehicles."

BE IT FURTHER RESOLVED: That the listed vehicle models also comply with the "California Motor Vehicle Emission Control and Smog Index Label Specifications" for the aforementioned model year (Title 13, California Code of Regulations, Section 1965).

BE IT FURTHER RESOLVED: That the listed vehicle models also comply with the "Malfunction and Diagnostic System Requirements--1994 and Subsequent Model-Year Passenger Cars, Light-Duty Trucks, and Medium-Duty Vehicles and Engines" (Title 13, California Code of Regulations, Section 1968.1) for the aforementioned model year.

BE IT FURTHER RESOLVED: That the vehicle manufacturer has demonstrated compliance with the exhaust emission standards at 50 degrees Fahrenheit as stipulated in "California Exhaust Emission Standards and Test Procedures for 1988 and Subsequent Model Passenger Cars, Light-Duty Trucks, and Medium-Duty Vehicles."

BE IT FURTHER RESOLVED: That for the listed vehicles, the manufacturer has submitted and the Executive Officer hereby approves the materials to demonstrate certification compliance with the Board's emission control system warranty provisions (Title 13, California Code of Regulations, Section 2035 et seq.).

Vehicles certified under this Executive Order must conform to all applicable California emission regulations.

The Bureau of Automotive Repair will be notified by copy of this order and attachment.

Executive Order A-325-6 dated November 4, 1997 is superseded and replaced by Executive Order A-325-6-1.

Executed at El Monte, California this // day of January 1998.

R. B. Summerfield, Chief Mobile Source Operations Division

Air Resources Board Supplemental Data Sheet Passenger Cars, Light Duty Trucks and Medium Duty Vehicles Model Year 1998

Manufacturer: GFI CONTROL SYSTEMS INC. Exh Eng Fam: WG9XA05.45BF Evap Fam: WFMXE0160BAF
All Engine Codes in Engine Family: CA 49s 50s X AB965 ORVR: Yes No X
Exh Std: CA Tier-1 TLEV LEV X ULEV SULEV, US EPA Tier-1
Veh Class(es): PCLDT1LDT2MDV1MDV2_X_MDV3MDV4MDV5
Single Cert Standard for Multi-Class Eng Family: N/A (specify: N/A, LDT1, MDV1, MDV2, MDV3, MDV4)
Fuel Type(s): DedicatedFlex FuelDual Fuel_X_Bi-FuelGasoline_X_Diesel
CNGLNGLPG_X_M85 Other (specify)
Exh Emiss Test Fuel(s): Indo X CBG CNG LPG X M85 Other (specify)
Diesel: 13 CCR 2282 40 CFR 86.113-90 40 CFR 86.113-90
Evaporative Emissions Test Procedure: California Federal_X
Service Accum: Std AMA Mod AMA Mfr ADP X Other (specify)
NMOG Test Procedure: N/A Std_X Equiv R/L Test Proc: SHED Pt Source_X_
Engine Configuration: V8 Displacement: 5.4 Liters 326 Cubic Inches
Valves Per Cylinder: 2 Rated HT: 235 @ 4250 RPM
Engine: Front X Mid Rear Drive: FWD RWD X 4WD-FT 4WD-PT
Exhaust ECS (e.g., MFI, EGR, TC, CAC): 2TWC (2), 2HO2S(2), EGR, SFI
(use abbreviations per SAE J1930 Jun93)

Engine Code (also list CA/49st/50st)	Vehicle Models (if coded see attachment)	Trans. (M5, A4 etc.)	ETW or Test Wt.	DPA or RLHP	Ignition (ECM/PCM) Part No.	EGR System Part No.	Catalytic Converter Part No.
MAAF1/8-46C GFI024F3 MJLSTN22.F3	F-150 PickUp GVWR 6050	A4	5750 lbm	16.9hp	F85F-12A650 A2-503 K1-122	F75E-9D475-CA	F85A-5E218-CB F85A-5E218-DB F85A-5G218-EB F85A-5G218-DB
						:	